TJ-2118L Shrink Wrapper

Automatic L-Bar Sealer with Closing Conveyor and Print Registration



INCLUDED FEATURES

- Easy-to-operate, customizable HMI touchscreen
- Factory-installed print registration for printed film
- Opaque film sensor for product detection
- Closing conveyor for small packages
- Variable frequency drives (VFDs) on the infeed, outfeed, and scrap take-up for independent speed control
- Automatic scrap take-up
- One-piece, heat-resistant, Teflon-coated alloy sealing blades for durability and easy cleaning
- Pneumatic seal head operation
- Easy-thread film carriage with adjustable film perforation wheels

SPECIFICATIONS

Model	TJ-2118L
Seal area	20" length × 17" width
Max. package height	4.72"
Maximum speed	25–30 pieces per minute
Conveyor speed	0–85 feet per minute (up to 30 PPM)
Film width	8" min. to 22" max.
Compatible films	Polyolefin shrink film, 30–200 gauge
Power	220V / 1 phase / 10 amp
Compressed air	80 psi
Machine dimensions	66.5" L × 32.5" W × 58.5" H
Warranty	2-year parts (conditions apply)

AVAILABLE OPTIONS

- Easy-clean belts and stainless steel construction
- Remote access HMI support